



Model	ENR-190
Product Type	Standalone NVR
Maximum Resolution	Local: up to 4MP; Remote: up to 10MP
Maximum Number of Cameras	16
Maximum Number of Video devices	16
Maximum Number of Clients	Local: 1, Remote: 2
License required	No
Free License	16
Display Layout Mode	Local: 1,2,4,9,12,16,1+5,1+7,1+12,2+4,2+8, Remote: 1,2,4,9,12,16,1+5,1+7,1+12,2+4,2+8
Local Live View performance	Please check "Standalone NVR Performance Validator" ( <a href="http://www.acti.com/SANVRPerformance">http://www.acti.com/SANVRPerformance</a> )
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client
Instant playback	Instant Playback in live view window (Remote client)
Compression	H.264
Network Protocol & Service	IPv4/v6, TCP, IP, UDP, HTTP, HTTPS, DHCP (Server/Client), PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, SMTP, UPnP, (To be available through future firmware upgrade)
Ethernet Port	LAN 1 : Ethernet (1000 Base-T) , RJ-45 connector, LAN 2 : Ethernet (10/100 Base-T) , RJ-45 connector
Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Event Speed-up Recording	Yes
Dual Stream Management	Yes
Maximum Recording Throughput	48 Mbps
Playback Control	Continuous forward and backward playback with speeds 0.5x/1x/2x/4x/8x/16x/32x, pause, stop
Synchronized Playback	16 channels
Video Export	AVI, RAW
Permission control	Unlimited number of users, Customizable permissions for user groups
Client PC Operating System	Windows 7, Windows 8
Server Operating System	Embedded Linux
Mobile Client Program	Mobile device application (ACTi Mobile Client) supports Live View, PTZ Control, Event/time based search and playback, Supported device(s) iPhone, iPad, iTouch, Android device
USB	2 port(s), USB 2.0
Language	Multi-Language

System Status Monitor	Real time status reports on remote browser
ONVIF Compliant	Yes, Profile S
Web Browser	IE 9.0 or newer
Local Access	HDMI monitor, USB keyboard & mouse
Power Source	AC 100-240V
Power Consumption	64 W (AC)
Mount Type	Rack mounts
HDD Bay	SATA, Max. 4 3.5" Disk(s)
Fan	Yes
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Warranty	2 Year(s)
Remote Access	Workstation, Web Client, Mobile Client
Approvals	CE, FCC, UL (for built-in power adapter)
Joystick	USB based joystick supported